

NEW Power Cook Gas Table Stove [Equipped with New Universal Burner] Specifications Table <RGC>

See pages 11.

RGC-096C



Model	External dimension (mm)			No. of top burners ^{※1}		Gas consumption		Gas Connection		Weight (kg)
	Width	Depth	Height	φ95	φ165	Town gas	LP gas	13A、12A	LP gas	
RGC-044C	450	450	200	—	1	13.4kW (11,500kcal/h)	12.2kW (0.88kg/h)	13mm rubber tube end	9.5mm rubber tube end	25
RGC-064C	600	450	200	2	—	10.5kW (9,000kcal/h)	9.3kW (0.67kg/h)	13mm rubber tube end※	9.5mm rubber tube end	26
RGC-094C	900	450	200	—	2	26.7kW (23,000kcal/h)	24.4kW (1.75kg/h)	20A	20A	43
RGC-096 (H) C	900	600	200(250)	1	2	32.0kW (27,500kcal/h)	29.1kW (2.08kg/h)	20A	20A	62
RGC-1264 (H) C	1,200	600	200(250)	2	2	37.2kW (32,000kcal/h)	33.7kW (2.42kg/h)	20A	20A	79
RGC-1265 (H) C	1,200	600	200(250)	2	3	50.6kW (43,500kcal/h)	45.9kW (3.29kg/h)	20A	20A	86

※1 Maximum pot diameter for φ95 burner is φ280mm and for φ165 burner is φ400mm.

■(H) is Height 250mm spec. (The price is the same).

■Screw connection for 094B, union connection for 096(H)B, 1264(H)B and 1265(H)B. ※13A only